

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously presented) A distributed virtual tandem switching system, comprising:

a centralized control and signaling interworking function (CS-IWF) device centrally serving a plurality of trunk inter-working function (T-IWF) devices, the CS-IWF device performing call control functions, providing a single connection between a narrowband signaling network and a packet network, interfacing narrowband and broadband signaling for call processing and control within the packet network so that telephone calls originating and terminating within a public switched telephone network are transmitted through the packet network, and communicating with the plurality of T-IWF devices via the packet network to send call setup information.

2. (Previously presented) The distributed virtual tandem switching system of claim 1, in which the narrowband signaling is SS7 signaling.

3. (Previously presented) The distributed virtual tandem switching system of claim 1, in which the broadband signaling is PNNI.

4. (Previously presented) The distributed virtual tandem switching system of claim 1, in which the broadband signaling is B-ISUP.

5. (Previously presented) The distributed virtual tandem switching system of claim 1, in which the broadband signaling is UNI.

6. (Previously presented) The distributed virtual tandem switching of claim 1, wherein the CS-IWF device dynamically facilitates setting up an individual switched virtual connection in the packet network.

7. (Previously presented) A distributed virtual tandem switching method for transporting voice across a data network, the method comprising:

receiving narrowband signaling at a centralized control and signaling interworking function (CS-IWF) device;

converting between narrowband signaling and broadband signaling for call processing and control within the data network;

forwarding from the CS-IWF device, via the data network, to at least one trunk inter-working function (T-IWF) device call processing information; and

forwarding the broadband signaling from the CS-IWF device to the data network so that telephone calls originating and terminating within a public switched telephone network are transmitted through the data network.

8. (Previously presented) The distributed virtual tandem switching method of claim 7, in which the narrowband signaling is SS7 signaling.

9. (Previously presented) The distributed virtual tandem switching method of claim 7, in which the broadband signaling is PNNI.

10. (Previously presented) The distributed virtual tandem switching method of claim 7, in which the broadband signaling is B-ISUP.

11. (Previously presented) The distributed virtual tandem switching method of claim 7, in which the broadband signaling is UNI.

12. (Previously presented) The distributed virtual tandem method of claim 7, further comprising dynamically setting up an individual switched virtual connection in the packet switching network.

13. (Previously presented) A computer readable medium storing a program for transporting voice across a packet network, comprising:

a receiving source code segment that receives narrowband signaling at a centralized control and signaling interworking function (CS-IWF) device;

a converting source code segment that converts between narrowband signaling and broadband signaling for call processing and control within the packet network;

a call management information forwarding code segment that communicates from the CS-IWF device to at least one trunk inter-working function (T-IWF) device via the packet network to send call management information; and

a forwarding source code segment that forwards the broadband signaling from the CS-IWF device to the packet network so that telephone calls originating

and terminating within a public switched telephone network are transmitted through the packet network.

14. (Original) The computer readable medium of claim 13, in which the narrowband signaling comprises SS7 signaling.

15. (Original) The computer readable medium of claim 13, in which the broadband signaling comprises PNNI.

16. (Original) The computer readable medium of claim 13, in which the broadband signaling comprises B-ISUP.

17. (Original) The computer readable medium of claim 13, in which the broadband signaling comprises UNI.

18. (Previously presented) The computer readable medium of claim 13, further comprising a switched virtual connection source code segment that dynamically sets up an individual switched virtual connection in the packet network.

19. – 20. (Canceled)